










Loose fittings

Type		Name	Weight [kg]	Counter parts		Material	Treatment	Nom.breaking load[kN]	Remarks
Multilash system		TB-3	12.5	Lashing eyes plate;D-ring; Lashing bar:LB-3S,LB-3V; Extension rod:ER-2		High tensile steel; Lashing bars: forged endfittings	Hot dip galvanized; Turnbuckle / bridge fitting: spindle greased only	Tension: 500 / 360	Lashing bars according to request, weight depends on length; ER-1;Length = 310mm
		TB-3-2	14.8						
		LB-3S		Turnbuckle:TB-3,TB-3-2; Extension rod:ER-2					
		ER-2	5.2	Turnbuckle:TB-3,TB-3-2; Lashing bar:LB-3S,LB-3V					
Jaw / hook lashing		TB-1A	13.3	Lashing eyes plate;D-ring; Lashing bar:LB-2S;					
		TB-1B	14.6						
		TB-1C	13.7						
		TB-2B	14.8						
		LB-2S		Turnbuckle:TB-1A,TB-1B...TB-E/65; Extension rod:ER-1					
ER-1		3.6	Turnbuckle:TB-1A,TB-1C,TB-E/65; Lashing bar:LB-2S						
Vertical lashing		TB-3	12.5	Lashing eyes plate;D-ring; Lashing bar:LB-3S,LB-3V; Extension rod:ER-2					
		LB-3V		Turnbuckle:TB-3,TB-3-2; Extension rod:ER-2					
		LB-3E LB-3V-1							
Equal lash		TB-E/65	20	Lashing eyes plate;D-ring;					
		LB-2S		Turnbuckle:TB-1A,TB-1C...TB-E/65; Extension rod:ER-1					
Advanced lashing		TB-2C	16.2	Lashing eyes plate;D-ring;					
		LB-2F		Turnbuckle:TB-2C					
Operating wrench/bar		SP-1	1	TurnbuckleTB-3,TB-3-2, TB-E/65, TB-1		16Mn	Hot dip galvanized oprimered on request		
		SP-2	2.6						
		L-1							
Type	Name	Min-Max distance[mm]	Weight	Counter parts	Material	Nom.breaking load[kN]	Treatment		
Bridge Fitting		BF-1	170-260	4.5	Container corner castings	Spindle:high tensile steel;Endfittings: Precision cast steel	Tension: 100	Hot dip galvanized; Spindle greased only	
		BF-2	170-440	8.6		Precision cast steel	Tension compress:400		