





















Loose fittings

Type	Name	Weight [kg]	Material	Remarks	Counter parts	Treatment	Nom. breaking load[kN]		
							Tension	Shear	
Manual twistlock	 T1	5.1	Housing;precision cast steel;locking bolt;forge high tensile steel		Left handle locking(Right handle locking also available)	Container corner casting,twistlock foundation,twistlock pocket	Hot dip galvanized	500	420
	 T2	6.7							
	 T3	5.45							
Dovetail twistlock	 T4-1	6.7		Dovetail angle 45°		Container corner casting,dovetail foundation	Hot dip galvanized	500	420
	 T4-2	6.86		Dovetail angle 45° for transversal shifting					
	 T5-1	7.42		Dovetail angle 55°					
	 T5-2	8.1		Dovetail angle 55° for transversal shifting					
	 T9	5.9							
One wire SAT	 T6	5.65		Locking pole;forge or preison cast high tensile steel;Housing;precision cast steel;Wire handle;stainless steel		Dual function	Container corner casting,twistlock foundations,	Hot dip galvanized	500
	 T6HC	7.5	Pressureless mechanism						
Fully symmetrical SAT	 T7	6.8	Dual function;full sym-meterical;housing for higher pressure force						
MID-LOCK	 T8	4.8	Midlock function						
Flatracks and storage bins	 SB-1	145	Structural steel		T-...	Shotblasted,primered and final grey coated			
	 FL-20'	1480		CSC safety approval; post with reflex film Pockets for forklift hanging	8 x SB-1				
	 FL-40'	2800		CSC safety approval; post with reflex film Gooseneck Tunnel	12 x SB-1				
Type	Name			Counter parts	Weight [kg]	Length[m]	Material		
Operating rods	 AP-1			T6,T6HC	0.2	3.05/5.26/7.5/10.16	Aluminum		
	 AP-2					1.8/5.1/7.7/10.5			
	 AP-3			T1,T2,T3		1.8/5.1/7.7/10.5			
Emerg-ency	 ET-1			T7/Turnbuckle	0.2		wood/45#		
	 ET-2			T7	1		Steel		